

CHALK

PINTY[®] PLUS

CHALK FINISH SPRAY PAINT

Wax, Varnish, Primer and Chalk Finish



CHALK FINISH

Chalk finish spray paint for decoration purposes.
Ultra matte finish with a velvety appearance.

Perfect for any surface including expanded polystyrene. It can be washed with soap and water within the first 15 minutes. Maximum coverage and fast drying. Water-based formulated, it is more respectful to the environment.

APPLICATIONS:

Allows decorating easily multiple surfaces in order to give a vintage touch to your objects. Ideal on wood, melamine, canvas, iron, plastic, cardboard and even on glass. As it does not contain aggressive solvents, it does not attack the expanded polystyrene (Polystyrene). In order to achieve a smooth finish surface, it is recommended to apply several thin layers, letting them dry and sanding them lightly until you obtain the desired texture.

TECHNICAL CHARACTERISTICS:

Performance 520/400ml = 2 m²
Drying time in 20 minutes, total drying in 1 hour.
Repainted with the same paint 30 min.
Repainted with another paint 24 hours.

ULTRA-MATTE FINISH



				
CK801 Mustard	CK793 Rose Garden	CK792 Pink Petal	CK827 Coral	CK804 Red Velvet
				
CK796 Pale Turquoise	CK797 Turquoise	CK795 Blue Indigo	CK835 Light Lavender	CK836 Dark Lavender
				
CK794 Mint Green	CK817 London Grey	CK803 Oliva Vintage	CK790 Chesnut Brown	CK789 Cream
				
CK791 Stone	CK798 Ash Grey	CK799 Black Plumb	CK788 Broken White	

VARNISH

Water-based varnish.
Protects surfaces painted with Chalk Finish



CK821

Varnish in spray for Chalk Finish Paints in aerosol cans. It is a water-based clear and quick-drying varnish. Protects the surface, is more environmentally friendly and has low odor, it is a non-toxic product. Matte finish. It does not yellow.

APPLICATIONS:

This novel formulation is suitable for use indoors. Protects, enhances and waterproofs any surface painted with Pintyplus Chalk Finish Paint. Strengthens the colours and protects from dirt.

TECHNICAL CHARACTERISTICS:

Spreading 520 / 400ml = 1.40 m²
Dry to the touch in 1 h. Total dry in 24 h.
Matte finish.

HOW TO USE:

The surface to be varnished must be completely dry. We recommend to wait before applying minimum 24 hours after the application of paint.

Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

RECOMMENDATIONS:

Use the varnish also to enhance the tone of the Chalk Finish. Highly recommended in damp or dirty environments. If you want to give an ultra matte look, combine Pintyplus Chalk Finish with this matte varnish.

PRIMER

It prepares any surface in order to paint afterwards.



CK820

It is a primer which prepares any kind of surface you want to paint with Pintyplus Chalk Finish Paint. It provides anchoring and prevents corrosion on metal surfaces.

APPLICATIONS:

It does not only give the necessary adhesion in order to paint comfortably with our Pintyplus chalk finish paints but at the same time, prevents from rust and stains of dirt. Suitable for surfaces such as wood, rigid plastic, melamine, formica, metals, etc. It can also be applied as a pore cover on wood, plaster, terracotta or any other porous surface.

TECHNICAL CHARACTERISTICS:

Spreading: 520 / 400ml 1.4 – 1.6 m² according to support.

Total drying in 1 hour.

Repainted before 1 hour or after 24 hours.

Matte white finish.

HOW TO USE:

The surface to be painted must be clean, dry and free of any contaminants. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

RECOMMENDATIONS:

For a perfect finish, repaint within 24 hours of its application.

*No usar sobre equipos conectados a la corriente y aplicar en lugares ventilados.
Una vez vacío, el aerosol debe depositarse en el contenedor amarillo.*





NOVASOL SPRAY S.A.

C/ Empalme, 27
43712 Llorenç del Penedès (SPAIN)
Tel. +34 977 677 305
www.pintyplus.com
novasol@novasolspray.com

