

EVOLUTION WATER-BASED

ACRYLIC RAL **EVOLUTION** PINTY PLUS

Water-based acrylic spray paint



EVOLUTION WATER-BASED

Water-based acrylic spray paint for domestic and professional applications.
Glossy Ral colors. Free of aggressive solvents. Low odor.
Recommended for all surfaces.

Two of its main characteristics are the versatility (it can be applied on any material and in a wide range of projects) and the ease of use (no experience needed). In addition, it offers great resistance and adherence, protecting painted objects effectively. The Water-based family consists of 22 Ral colors, two varnishes and a primer.

APPLICATIONS:

Ideal for any surface. Being water-based, it will not damage delicate materials as it does not contain any solvent. Ideal for jobs in industrial processes. By removing solvents from spray products, the health of workers will be better protected.

RAL coded colors for common applications and usual repairs at home. Ideal also in the professional field. It can be painted both indoors and outdoors ensuring a great protection in the two environments.

TECHNICAL CHARACTERISTICS:

Spreading spray 520/400ml: 2m²


Drying time: 15 minutes

Total drying time: 1h

Repainted after 15 min.

Heat resistance: 90°C

Product shelf life: 10 years

								
RAL 1015 Light ivory	RAL 1021 Sunny yellow	RAL 1028 Melon yellow	RAL 2004 Pure orange	RAL 3000 Flame red	RAL 3020 Traffic red	RAL 5010 Gential blue	RAL 5015 Sky blue	RAL 5017 Traffic blue
								
RAL 6005 Moss green	RAL 6018 Yellow green	RAL 6029 Mint green	RAL 7001 Silver grey	RAL 7012 Basalt grey	RAL 7016 Anthracite grey	RAL 7035 Light grey	RAL 8011 Nut brown	RAL 8017 Chocolate brown
								
RAL 9005 Jet black Gloss	RAL 9005 Jet black Matte	RAL 9006 White aluminium	RAL 9010 Pure white Gloss	RAL 9010 Pure white Matte	RAL 9016 Traffic white	B199 Clear Varnish Gloss	M199 Clear Varnish Matte	

EVOLUTION WATER-BASED

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants.

Shake the can vigorously during 1 minute after the mixing balls sound (except the gloss varnish, which does not contain it). Spray from a distance of 25/30cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed, reverse the can and push the nozzle until the gas comes out in order to prevent nozzle clogging.

TIPS:

Before applying the layer of Pintyplus Evolution Water-Based Paint and in order to achieve an optimal anchoring, it is recommended to apply a previous layer of primer, either if the surface is smooth, slightly porous or very porous.

On a previously painted surface and before applying a new layer of paint, we recommend a light sanding to ease the bonding to the surface. If needed, remove entirely the anterior layer of paint. Proceed with a harder sanding or use a stripping product such as our Pintyplus TECH Paint Stripper.

Water-based primer that ensures a perfect adherence, a smooth finish and a high resistance. Free of aggressive solvents.
Very low odor. Suitable for any surface.



APPLICATIONS:

Ideal for priming any surface, including those more delicate surfaces which do not support the action of corrosive solvents. It is used to cover the pore of very porous surfaces, achieving a good anchoring on those surfaces without pore.

It maximizes the most important characteristics of paints: anchoring, adhesion, resistance, protection, smooth finish and ease of use. It is highly recommended to use it on any surface before painting with Pintyplus Evolution Water-based Paints.

TECHNICAL CHARACTERISTICS:

Spreading spray 520/400ml: 2 m²

Matt finish

Drying time: 1h

Repainted after 1 hour

Product shelf life: 10 years



IW101

HOW TO APPLY:

Shake the can vigorously during 1 minute after the mixing balls sound (except the gloss varnish, which does not contain it). Spray from a distance of 25/30cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed, reverse the can and push the nozzle until the gas comes out in order to prevent nozzle clogging.

TIPS:

Before applying the layer of Pintyplus Evolution Water-Based Paint and in order to achieve an optimal anchoring, it is recommended to apply a previous layer of this primer either if the surface is smooth, slightly porous or very porous.

On previously painted surfaces and before applying a new layer of paint, we recommend a light sanding to ease the bonding to the surface. If needed, remove entirely the anterior layer of paint: proceed with a harder sanding or use a stripping product such as our Pintyplus TECH Paint Stripper.

*Do not use on devices connected to the current and apply in ventilated areas.
Once empty, the can should be deposited in the yellow container.*





NOVASOL SPRAY S.A.

C/ Empalme, 27
43712 Llorenç del Penedès (SPAIN)
Tel. +34 977 677 305
www.pintyplus.com
novasol@novasolspray.com

