

# GREENOX

**Greenox**<sup>®</sup>  
SPRAY

Maintenance and lubrication



# GREENOX

## LUBRICANT

*"All in one" quality lubricant spray for household and DIY purposes.*

It is the ideal lubricant to have it always at hand. The format is perfect for keeping it in confined spaces such as in a drawer or in the glovebox of your car.

### APPLICATIONS:

Special product to avoid corrosion and achieve a constant protection. Eliminates friction and smoothes joints and cogs. Lubricates locks, guns, fishing reels, etc Highly penetrating with hydrofugal characteristics. It enables engines which have got wet to be started.

### TECHNICAL CHARACTERISTICS:

Spray can 210/150ml.

### HOW TO APPLY :

Shake slightly the can and spray till forming a film in order to lubricate and protect metallic surfaces.

### TIPS:

To loosen rusted stuck seized parts, clean the piece and spray generously. Wait about two minutes for the product to penetrate.

To displace moisture, apply the product in excess till drips off, free of moisture.



## ICE REMOVER

*The essential tool for the winter months. Ice remover and defrosting agent for windscreens and locks.*

As a defrosting agent and ice remover, the formulation especially developed for aerosols acts instantaneously on windscreens, windows, locks, headlights, mirrors and any part of the vehicle exposed to temperatures below freezing point. A small amount is sufficient to melt frost, snow or ice.

### DIRECTIONS OF USE:

Before applying the product, remove snow in excess with a plastic scraper.

After this, shake the aerosol and spray 20 cm from the surface, applying the product from the top of the windscreen. Wait a few minutes and remove it with a plastic scraper or any similar object. If the frost layer is very thick, repeat the process.

To complete it, turn on the windscreen wiper to eliminate any remaining frost.

### TIPS:

After parking the car outdoors, apply a thin layer on the windscreen and any other surface, which you want to protect. This action will help prevent or delay the layer of frost.



# GREENOX

*Do not use on devices connected to the electrical network and apply in ventilated areas.*

*Once empty, the spray must be deposited in the yellow container.*





---

**NOVASOL SPRAY S.A.**

P. I. L'Empalme. 43712 Llorenç del Penedès (ESPAÑA) Tel. +34 977 677 305 [www.novasolspray.com](http://www.novasolspray.com)