

TECH

PINTY[®] PLUS TECH

Technical aerosol paints



ZINC PRIMER

Cold galvanized zinc primer spray. Anticorrosive gloss primer of long duration based on zinc powder and resins.



Z169 Silver
270cc. Ref. 778
520cc. Ref. 737

High yield coating rich in zinc. Minimum 99% pure zinc. It adheres electro-chemically to the metallic support. Excellent resistance to the elements. Elevated hardness and flexibility.

APPLICATIONS:

Specially indicated for maximum protection of metallic surfaces from corrosion such as: metallic structures, fences, deposits, welding joints, repairs of galvanized pieces, railroad equipment, etc.

TECHNICAL CHARACTERISTICS:

Spreading 270/200ml = 0,7 m². 520/400ml = 1,4 m²

Heat-resistant up to 600°C.

Drying time in 1 hour.

Repainted in 1 hour.

HOW TO APPLY:

Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. The surface to be painted must be clean, dry and free of any contaminants. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper. For a colored finish, repaint with Pintyplus Basic Paint or Evolution Acrylic Paint. On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

STAINLESS STEEL PRIMER

Stainless spray is a gloss acrylic anticorrosive primer with an appearance similar to stainless steel.



I150 Silver
Ref. 213

It contains 316L stainless steel metallic pigments and provides a very good hiding power. Quick dry. It offers excellent resistance to scratches and abrasion.

APPLICATIONS:

Ideal for covering stainless steel welding, storage tanks, steel structures, fences, etc.

TECHNICAL CHARACTERISTICS:

Spreading 520/400ml = 2 m²

Drying time in 30 minutes.

Repainted in 30 minutes.

HOW TO APPLY:

Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. The surface to be painted must be clean, dry and free of any contaminants. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it. To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

GALVAZINC PRIMER

Cold galvanized Anticorrosive galvanic primer based on aluminum resins and additives.



G150 Silver Ref. 738 G151 Gold Ref. 739

Elevated antioxidant protection on metallic surfaces. Smooth, uniform and gloss finish. Excellent resistance to the elements.

APPLICATIONS:

Used to protect metallic surfaces from corrosion: metallic structures, fences, tanks, agricultural machinery, railroad equipment, pipes, fasteners, etc. Used for welding and galvanized retouching.

TECHNICAL CHARACTERISTICS:

Spreading 520/400ml = 2 m²

Heat-resistant up to 600°C (Silver) 200°C (Gold)

Drying time in 15 minutes.

Repainted in 30 minutes.

HOW TO APPLY:


Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. The surface to be painted must be clean, dry and free of any contaminants. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it. To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper. For a colored finish, repaint with Pintyplus Basic or Pintyplus Evolution.

UNIVERSAL PRIMER

Anticorrosive alkyd universal primer spray. Matte finish.



I113 Grey
270cc. Ref. 209
520cc. Ref. 297

I101 White
520cc. Ref. 214

I112 Red
520cc. Ref. 735

Free from chrome and lead components. Quick dry.

APPLICATIONS:

Suitable for use on iron objects and surfaces to be protected from any surrounding (damp, industrial, marine, etc.) achieving a longer life and making a better use of the finish paint.

TECHNICAL CHARACTERISTICS:

Spreading 270/200ml = 0,7 m². 520/400ml = 1,4 m²

Drying time in 48 hours.

Repainted before 1 hour or after 48 hours.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

For a colored finish, repaint with Pintyplus Basic Paint or Evolution Acrylic Paint. On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

TECH

PRIMER FOR PLASTICS



I199 Colorless
Ref. 295

Colorless primer spray for plastic. Obtain the best anchorage before applying the final finish.

APPLICATIONS:

Ideal for models and modeling, automotive plastic parts (bumpers, spoilers, mirrors, etc) as well as any plastic object to be painted (furniture, hard plastic suitcases, toys, etc..) Shake for 1 minute.

TECHNICAL CHARACTERISTICS:

Spreading 520/400ml = 3-4 m² depending on the support.

Superficial drying time in 15 min.

Repainted after 15 min.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Let it dry for 10-15 minutes and then it can be painted with any acrylic or synthetic paint. Shake the can for about 30 seconds before use.

TIPS:

For a colored finish, repaint with Pintyplus Basic Paint, Pintyplus Evolution Acrylic Paint, Evolution Water-Based Paint and if you wish a vintage look, repaint with Pintyplus Chalk Paint. Before applying it is advisable to lightly sand the surface and clean it with a degreaser.

WROUGHT IRON EFFECT PAINT



FJ104 Black Ref. 847
FJ113 Grey Ref. 848
FJ826 Blue Ref. 826



FJ925 Green Ref. 925
FJ825 Red Ref. 825

Two in one primer and wrought iron effect paint.
Ultra matte epoxy paint to decorate and protect metallic surfaces.

Thick and tough finish which produces an antique iron effect. Two in one: primer and finish. Resistant to abrasion. Excellent durability outdoors.

APPLICATIONS:

Quick dry paint with a very good adherence on metallic supports. Decorates and protects: railings, post boxes, exterior lamps, iron-gates, gardening stands, etc.

TECHNICAL CHARACTERISTICS:

Spreading 52/400ml = 1 m²

Surface drying time in 15 minutes, total 24 hours.

Repainted after 30 minutes.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On plastic or galvanized steel apply a specific primer to ensure perfect adhesion. On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

ANTI-STAINS PAINT



X101 White
Ref. 293

Anti-moisture and anti-stains paint. Matte white paint to cover and seal definitely tough stains on walls and ceilings.

High coverage product. Does not yellow. Inhibits moisture.

APPLICATIONS:

It can be applied on concrete, drywall, plaster and wood and it is also useful in masonry. Ideal for covering stains: pen, smoke, nicotine, moisture, etc. Clean previously the surface before its application.

TECHNICAL CHARACTERISTICS:

Spreading 520/400ml = 2 m²

Drying time in 2 hours.

Repainted after 10 min.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants.

Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags.

TIPS:

Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

PAINT STRIPPER



Ref. 292

The paint stripper spray is a super active low toxicity paint remover suitable for DIY which can be eliminated with water.

APPLICATIONS:

Quick action to remove all types of paint: alkyd, acrylic, cellulose, vinyl, with oil, polyester and polyurethane, epoxy varnish, etc. Decarbonizing-cleaning agent suitable for engines, injectors, carburetors, mechanical seals, etc.

TECHNICAL CHARACTERISTICS:

Format: 520/400ml

HOW TO APPLY:

Shake the can vigorously during 1 minute after the mixing balls sound.

Spray the product plenty on the surface to be stripped and leave the product for a few minutes (between 1 and 15 min. depending on the type of paint to be stripped, thickness, number of layers ...). Finally eliminate it and wash the surface with soap and water. Apply a second layer if you desire to remove toughest older parts.

TIPS:

After a few minutes and in order to see the degree of stripping, you can remove with the help of a cloth and some water the stripped paint. You can apply the product again as many times as necessary.

If there are several layers of paint, you can also remove them all. The time you leave the product to act on the surface will determine the intensity of the paint stripping.

TECH

HIGH TEMPERATURE PAINT



A150 Silver Satin
270cc. Ref. 786
520cc. Ref. 201

A104 Black matte
270cc. Ref. 785
520cc. Ref. 204

Spray paint for supports exposed to high temperatures.
The colours withstand temperatures up to 600°C.

APPLICATIONS:

Ideal for use on surfaces liable to withstand high temperatures: exhaust pipes, heaters, etc.

TECHNICAL CHARACTERISTICS:

Spreading 270/200ml = 1 m². 520/400ml = 2 m²

Surface drying time in 30 minutes, total 1 hour.

Repainted after 30 minutes.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging. After application, the temperature of the painted surface must be increased gradually to reach its maximum enabling the paint to crosslink.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

WHITE RADIATOR PAINT



RAL 9010
Ref. 151

White radiator spray paint, quick dry gloss white acrylic enamel.
Provides high temperature resistance up to 90°C.

Fast drying white gloss acrylic enamel.

APPLICATIONS:

Ideal for painting, retouching and for the preservation of all types of radiators, both cast and aluminum. Useful for heating tubes, heaters, etc. Clean the area, before its application.

TECHNICAL CHARACTERISTICS:

Spreading 520cc = 2 m²

Drying time after 15 min.

Repainted after 5 min.

Heat-resistant up to 100°C.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

INOX HOUSEHOLD APPLIANCES



E150 Inox
Ref. 150

Quick dry stainless steel finish spray paint.
Prevents oxidation.

APPLICATIONS:

Ideal to rejuvenate your old appliance giving it an elegant, modern look of stainless steel. Before using the product, clean the surface to be painted. Let it dry a few minutes between coats. Do not clean the surface with aggressive products.

TECHNICAL CHARACTERISTICS:

Spreading 520/400ml = 2 m²

Drying time in 30 min.

Repainted after 30 min.

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it. Once painted do not clean the surface with aggressive products.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

WHITE HOUSEHOLD APPLIANCES



RAL 9016
270cc. Ref. 148
520cc. Ref. 149

Quick dry antirust spray paint.
White gloss finish.

APPLICATIONS:

Ideal for the maintenance of all household appliances with paint damages or deteriorations.

TECHNICAL CHARACTERISTICS:

Spreading 270/200ml = 1 m². 520/400ml = 2 m²

Drying time 15 min.

Repainted after 5 minutes

HOW TO APPLY:

The surface to be painted must be clean, dry and free of any contaminants. Clean the rust and the scales, if any, with a wire brush. Remove grease stains with solvent. Shake the can vigorously during 1 minute after the mixing balls sound. Spray from a distance of 25/30 cm, applying thin and quick layers, first horizontally and then vertically. It is advisable to spray two thin layers instead of one thick layer in order to obtain uniform coverage and avoid paint sags. Once the operation is completed reverse the can and push the nozzle until only gas comes out in order to prevent nozzle clogging.

TIPS:

On painted surfaces, if properly adhered proceed with a light sanding to facilitate adherence, and if poorly adhered, remove it.

To facilitate cleaning of the surface of paint residues, we recommend using Pintyplus Tech Paint Stripper.

PERMANENT ADHESIVE

Permanent adhesive spray solvent base with modified synthetic rubber and resins



Ref. 740

Especially recommended for 'do-it-for-yourself' and industry. Format 520cc/400ml.

APPLICATIONS:

Permanent bonding with maximum performances having (maintaining, keeping...) the same characteristics as a normal contact glue (adhesive). Permits to join in a resistant, durable and flexible way all types of materials: wood, metal, plastic, rubber foam, leather, fabric, ceramics, etc.

TECHNICAL CHARACTERISTICS:

Format: 520/400ml.

HOW TO APPLY:

Before using the product, shake the can vigorously for one minute.

Apply a thin layer of the adhesive onto each surface to be join. Wait until the solvent evaporates. Under normal working conditions the evaporation time range is between 1 up to 5 minutes. After this time has passed, the interval to join the surfaces together is of 2 hours. The times depend on the materials used, environmental conditions and the amount of adhesive applied.

TIPS:

Do not use on devices connected to the electrical network and apply in ventilated areas. Once empty, the spray can must be deposited in the yellow container

GRAFFITIS REMOVER

Spray graffiti's remover very suitable for household
Low in toxicity. Can be eliminated with water.



Ref. 805

APPLICATIONS:

Suitable for removing all types of paint: alkyd, acrylic, cellulose, vinyl, with oil, polyester and polyurethane, epoxy varnish, etc.

TECHNICAL CHARACTERISTICS:

Format: 270/200ml

HOW TO APPLY:

Shake the can vigorously during 1 minute after the mixing balls sound.

Spray the product plenty on the surface to be stripped and leave the product for a few minutes (between 1 and 15 min. depending on the type of paint to be stripped, thickness and number of layers). Finally eliminate it and wash the surface with soap and water. Apply a second layer if you desire to remove the toughest older parts.

TIPS:

After a few minutes and in order to see the degree of stripping, you can remove with the help of a cloth and some water the stripped paint. You can apply the product again as many times as necessary.

If there are several layers of paint, you can also remove them all. The time you leave the product to act on the surface will determine the intensity of the paint stripping.

FLUORESCENT MARKER 360°

Fluorescent marker with 360° multidirectional valve
for temporary marking and signposting



Temporary matte finish paint to mark different elements on a wide range of surfaces providing high luminosity. It offers excellent paint coverage and is resistant to low temperatures. High capacity fluorescent colours with a greater visibility allowing the reading of signs, letters or numbers easily. Provided with security cap and 360° valve to enable spraying in all directions, even upside down.

TECHNICAL CHARACTERISTICS:

Spreading 650/500ml = 2 m²

Drying time in 10 minutes.

HOW TO APPLY:

It can be used in very different fields: mining and quarries; construction infrastructures and public works; for the maintenance of motorways and roads; in geological studies and in the industry. It can be applied on asphalt, concrete, stone, sand, wood, metal, etc.

TIPS:

After each application, clean the head with a piece of paper to prevent clogging.



T107
Red
Ref. 250



T118
Blue
Ref. 252



T136
Green
Ref. 253



T143
Orange
Ref. 255



T146
Yellow
Ref. 254



T184
Fuchsia
Ref. 251



T101
White
Ref. 271

TECH

EVENTS MARKER 360°

Fluorescent marker with 360° multidirectional valve for ephemeral marking. Average useful life of 5 days.



Matte fluorescent paint for ephemeral marking on a large number of surfaces. The time in which the painting will be visible will depend on the traffic, the environmental conditions and the use which is given to it. Its average useful life is about 5 days.

APPLICATIONS:

Indicated for ephemeral signaling and marking. Among its applications we highlight the temporary marking of sport events, the signposting of public works and road incidents. It can be applied on asphalt, stone, concrete, sand, wood, metal and all types of surfaces.

TECHNICAL CHARACTERISTICS:

Spreading 650/500ml = 2 m²

Total drying in 20 minutes.

HOW TO USE:

Shake the aerosol can vigorously for 1 minute after hearing the mixing balls sound. Apply in any directions, even upside down.

TIPS:

After each use clean the nozzle with a paper or rag to avoid clogging.



T143
Orange
Ref. 822



T146
Yellow
Ref. 824



T184
Fuchsia
Ref. 823




The difference between the conventional Fluorescent marker and the Event Marker is its useful life. Although both are temporary paints, the Event Marker is more ephemeral, lasts only a few days while the conventional marker can last several weeks.

TECH

SEALER

Sealing and waterproofing paint for fissures,
cracks or crevices.



	Black Ref. 681
	White Ref. 680
	Grey Ref. 682

Thick coating for sealing fissures, cracks or crevices when they appear in places that must be insulated from water, other liquids or gaseous elements: terraces, roofs, pipes, walls, brickwork, etc. Easy to use, it is fast drying and can be repainted once the paint has dried.

APPLICATIONS:

Especially suitable for sealing or waterproofing outdoor surfaces or structures that must prevent the passage of water. High sealing and insulating efficiency.

TECHNICAL CHARACTERISTICS:

Size 650/500ml
Spreading 3 m²
Heat resistance 100°C
Drying time for small crevices: 2h
Drying time for large crevices: 5h
Repainting after 72h
White, black and grey colors

HOW TO APPLY:

Clean rust and scale, if any, with a wire brush. Remove grease stains with solvent. The surface to be painted must be clean, dry and free of any dirt. Shake the can vigorously for 1 minute after hearing the mixing balls.

Spray from a distance of 25/30 cm., apply thin and quick layers, first horizontally and then vertically. It is advisable to apply two thin layers instead of a thick one, this way you will achieve a smooth finish coating avoiding product runs.

Once finished, turn the can upside down and press until only gas comes out to clean the nozzle.

RECOMENDATIONS:

Apply several coats until the desired thickness is achieved, depending on the application. If the crack or crevice is small, you will need less product, if it is larger, you will need more quantity. Let the product dry 5 minutes between coats.

Apply coats until the crack is sealed. If the product runs due to accumulation, this will not affect the sealing.

We must wait until the paint is completely dry before repainting.

Do not use on equipment connected to power and apply in well ventilated places.

Once empty, the can should be deposited in the yellow container.





NOVASOL SPRAY S.A.

C/ Empalme, 27
43712 Llorenç del Penedès (SPAIN)
Tel. +34 977 677 305
www.pintyplus.com
novasol@novasolspray.com

